



GH-8CC Series
8" Down Light

Type: _____
 Project: _____
 Catalog#: _____


Main Features

- Thermally engineered heatsink is robust and offers cooler operation
- High grade diffuser provides uniform light and greatly illuminates environment
- Glareless reflector creates visual comfort, cut-off angle <25°
- Can be ceiling or pendant mounted



Technical Information

GH-8CC



Specification Features

Model	GH-8CC-20	GH-8CC-40
Lumen Output	2400 lm	4400 lm
Power Consumption	21 W	38 W
Efficacy	114 lm/W	116 lm/W
Colour Temperature (CCT)	3000K, 3500K, 4000K	3000K, 3500K, 4000K
Dimensions	Ø 232 x 265	Ø 232 x 265
Voltage	26 V (24 - 28 V)	33 V (30 - 36 V)
Current	700 mA	1050 mA
Beam (Diffuser / Reflector)	F: 80° / R: 60°	F: 80° / R: 60°
Certification	cULus, RoHS, CE	cULus, RoHS, CE
IP Rating	40	40
Warranty	5 Years	5 Years

Order Form

Series	Model	Beam	Colour	Option
<input checked="" type="checkbox"/> GH	<input type="checkbox"/> 8CC-20	<input type="checkbox"/> 80° (Diffuser)	<input type="checkbox"/> 3000K	<input type="checkbox"/> 0-10V Dimming
	<input type="checkbox"/> 8CC-40	<input type="checkbox"/> 60° (Reflector)	<input type="checkbox"/> 3500K	<input type="checkbox"/> TRIAC
			<input type="checkbox"/> 4000K	