



GS-SlimR
Ultra-thin Rigid Strip Light



Type: _____
 Project: _____
 Catalog#: _____


Main Features

- Perfect for interior decorative lighting applications
- Touch dimming of 100%, 50%, 25%, 0%
- Available in 4 different lengths

Technical Information

GS-SlimR

8 / 12 / 34 / 46 inches



Specification Features

Model	GS-SlimR8	GS-SlimR12	GS-SlimR34	GS-SlimR46
Lumen Output (lm)	77 lm (48 lm/W)	115 lm (48 lm/W)	346 lm (48 lm/W)	466 lm (48 lm/W)
Power Consumption (W)	1.6W	2.4W	7.2W	9.7W
Colour Temperature (CCT)	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K
Input Voltage	12V DC	12V DC	12V DC	12V DC
PFC	> 0.90	> 0.90	> 0.90	> 0.90
Dimensions	8" x 7/18" x 3/8"	12" x 7/18" x 3/8"	34" x 7/18" x 3/8"	46" x 7/18" x 3/8"
Beam Angle	50°	50°	50°	50°
IP	40	40	40	40
Certification	cULus	cULus	cULus	cULus
Warranty	5 Years	5 Years	5 Years	5 Years

Order Form

Series	Model	Voltage	Colour
<input checked="" type="checkbox"/> GW	<input type="checkbox"/> SlimR8	<input type="checkbox"/> 12V DC	<input type="checkbox"/> 3000K
	<input type="checkbox"/> SlimR12		<input type="checkbox"/> 4000K
	<input type="checkbox"/> SlimR34		<input type="checkbox"/> 5000K
	<input type="checkbox"/> SlimR46		