

GDL-P - Prime Downlight

Type: _____

Project: _____

Catalog #: _____



Main Features

- Ensures high efficiency output without glare
- 6 models to choose from: glareless tilt, pin hole, basic tilted, Ø95 wallwasher, Ø80 wallwasher, and cardan light
- White, silver, gold and rose gold

Model	GDL-P
Lumen Output	850 lm
Colour Temperature (CCT)	3000K, 3500K, 4000K
Power Consumption	10W
CRI	80
Input Voltage	120-277V AC
IP	20
Angle	15°, 25°, 120°
Certification	cETLus, CE, RoHS



Order Form

Series	Wattage	Voltage	Beam Angle	Colour Temperature	Trim	Trim Colour*
<input type="checkbox"/> GDL-P	<input type="checkbox"/> 10W	<input type="checkbox"/> 120-277V AC	<input type="checkbox"/> 15°	<input type="checkbox"/> 3000K	<input type="checkbox"/> Glareless Tilt	<input type="checkbox"/> White
			<input type="checkbox"/> 25°	<input type="checkbox"/> 3500K	<input type="checkbox"/> Pin Hole	<input type="checkbox"/> Silver
			<input type="checkbox"/> 120°	<input type="checkbox"/> 4000K	<input type="checkbox"/> Basic Tilted	<input type="checkbox"/> Gold
					<input type="checkbox"/> Ø95 Wallwasher	<input type="checkbox"/> Rose Gold
					<input type="checkbox"/> Ø80 Wallwasher	
					<input type="checkbox"/> Cardan Light	*only available for the glareless tilt