



GS-SlimR - Ultra-thin Rigid Strip Light

Type: _____

Project: _____

Catalog #: _____




Main Features

- Perfect for interior decorative lighting applications
- Touch dimming of 100%, 50%, 25%, 0%
- Available in 4 different lengths

Model	GS-SlimR8	GS-SlimR12	GS-SlimR34	GS-SlimR46
Lumen Output	77 lm (48 lm/W)	115 lm (48 lm/W)	346 lm (48 lm/W)	466 lm (48 lm/W)
Power Consumption	1.6W	2.4W	7.2W	9.7W
Colour Temperature	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K	3000K, 4000K, 5000K
Input Voltage	12V DC	12V DC	12V DC	12V DC
PFC	> 0.90	> 0.90	> 0.90	> 0.90
Dimensions	8" x 7/18" x 3/8"	12" x 7/18" x 3/8"	34" x 7/18" x 3/8"	46" x 7/18" x 3/8"
IP	40	40	40	40
Beam Angle	50°	50°	50°	50°
Certification	cULus	cULus	cULus	cULus
Warranty	5 Years	5 Years	5 Years	5 Years

Technical Information

8 / 12 / 34 / 46 inches



Order Form

Series	Model	Voltage	Colour
<input type="checkbox"/> GS	<input type="checkbox"/> SlimR8	<input type="checkbox"/> 12V DC	<input type="checkbox"/> 3000K
	<input type="checkbox"/> SlimR12		<input type="checkbox"/> 4000K
	<input type="checkbox"/> SlimR34		<input type="checkbox"/> 5000K
	<input type="checkbox"/> SlimR46		

Accessories

Adaptors

ACDC24-24 - 24W plug in adaptor
ACDC48-24 - 48W Plug in adaptor



Power Connector

GS-SlimPWR - 98" long power feed



Extension Connector

GS-SlimCTR12 - 12" extension connector
GS-SlimCTR39 - 39" extension connector



Touch Dimmer

GS-SlimDM - Touch dimming section

