



GDL-SPL-M Scoop Module

Type: _____
 Project: _____
 Catalog#: _____






Main Features


- Simple assembly
- Accommodate scoop and adjustable down light fixtures
- 40% reduction in power consumption compared to traditional fixtures

Technical Information


GDL-SPL-M



1X1 housing



1X2 housing



1X3 housing

Specification Features

Model

GDL-SPL-M

Lumen Output	2350 lm
Power Consumption (W)	26W
Colour Temperature (CCT)	3000K, 3500K, 4000K
CRI	80
Input Voltage	120V AC
PFC	0.90
Dimensions (mm)	134 x 155 x 136 mm
Weight	910 g
IP Rating	20
Beam Angle	25°, 38°
Certification	cETLus, RoHS, CE
Warranty	5 Years

Order Form

Series	Model	Wattage	Voltage	Beam Angle	Colour	Fixture Option
<input checked="" type="checkbox"/> GDL	<input type="checkbox"/> 26SPL-M	<input type="checkbox"/> 26W	<input type="checkbox"/> 120V AC	<input type="checkbox"/> 25° <input type="checkbox"/> 38°	<input type="checkbox"/> 3000K <input type="checkbox"/> 3500K <input type="checkbox"/> 4000K	<input type="checkbox"/> Black <input type="checkbox"/> White